

# UST Bench Brush

330 mm, Soft, Yellow



Item Number: 45816

This ULTRA SAFE TECHNOLOGY (UST) Bench Brush with Ultra Filament Security ensures effective sweeping of fine dry particles from conveyor belts, food-preparation surfaces, tables and equipment in high-risk areas. All UST brushes feature a unique bristle system that minimises the risk of contamination and bristle loss.

## General Information

Bristle stiffness	Soft
Colour	Yellow
Material	Polyester (PBT), Glass reinforced, Polypropylene
UNSPSC Code	47131605
Country of Origin	Denmark

## Product Dimensions

Visible bristle length	57 mm
Product Length/Depth	330 mm
Product Width	35 mm
Product Height	135 mm
Net Weight	0.18 kg

## Packaging & Shipping Details

Box Quantity	10 Pcs.
Quantity per Pallet (80 x 120 x approx.180 cm)	960 Pcs.
Quantity Per Layer (Pallet)	80 Pcs.
Box Length/Depth	380 mm
Box Width	290 mm
Box Height	135 mm
Plastic Packaging (Recycling Symbol "4") LDPE per Pcs.	0.0048 kg
Cardboard Packaging (Recycling symbol "20" PAP) per Pcs.	0.0247 kg
Total Tare Weight	0.0295 kg
Gross Weight	0.21 kg
Cubic metre	0.001559 M3
GTIN-13 Number	5705020458163
GTIN-14 Number (Box quantity)	15705020458160
Customs Tariff Number	96039099

Item Number: 45816

## Compliance & Standard Details

Complies with (EC) 1935/2004 on food contact materials <sup>1</sup>	Yes
Complies with EU Regulation 2023/2006/EC of Good Manufacturing Practice	Yes
Complies with FDA Regulation CFR 21 <sup>1</sup>	Yes
Complies with UK 2019 No. 704 on food contact materials	Yes
Complies with REACH Regulation (EC) No. 1907/2006	Yes
Complies with California Proposition 65	Yes
Complies with Halal and Kosher	Yes
PFAS intentionally added	No

## Technical Data

Handle/Grip Length	140 mm
--------------------	--------

## Usage Limits

Max. usage temperature (food contact)	80 °C
Max usage temperature (non food contact)	80 °C
Recommended sterilisation temperature (Autoclave)	121 °C
Max. cleaning temperature (Dishwasher)	93 °C
Max. drying temperature	100 °C
Min. usage temperature <sup>3</sup>	-20 °C
Max. pH-value in Usage Concentration	10.5 pH
Min. pH-value in usage concentration	2 pH

## Design & Patent Registration Details

Design Registration No.	EU 002189654-0001, EU 002650838-1-4, US D838995, GB 9002650830001-4, GB 900265505800001-
Pat. Pending/Patent No.	EP2816930 validated in DE, FR, GB and DK. US9204712 EP2816929 validated in DE, FR, GB and DK. US9357831

## Sustainability Details

Product Recycling Symbol "7", Miscellaneous Plastics	Yes
--	-----

New equipment should be cleaned, disinfected, sterilised and any labels removed, as appropriate to its intended use, e.g. high risk vs. low risk food production areas, general hospital areas vs. intensive care units, before use.

1. See Declaration of Compliance for further details on food contact

3. Do not store the product below 0° Celsius.

