

# Flexible Handle, stainless steel

Ø5 mm, 755 mm, White



**Item Number: 53515**

A flexible rod for cleaning curved pipes such as sight-glasses on large tanks and transfer hoses. Can be used with Vikan tube cleaner heads (5354x, 5356x, 5365x, 5368x, 5391x, 5394x and 5396x). Connected by a screw thread and can be extended in increments of 750 mm by attaching product no. 5346.

## General Information

<b>Colour</b>	White
<b>Material</b>	Stainless Steel (AISI 304), Polypropylene, Stainless Steel (AISI 303Cu)
<b>Country of Origin ISO Code</b>	DK
<b>Country of Origin</b>	Denmark

## Product Dimensions

<b>Product Length/Depth</b>	755 mm
<b>Product Width</b>	5 mm
<b>Product Height</b>	5 mm
<b>Net Weight</b>	0.12 kg

## Packaging & Shipping Details

<b>Box Quantity</b>	10 Pcs.
<b>Quantity per Pallet (80 x 120 x approx.180 cm)</b>	600 Pcs
<b>Quantity Per Layer (Pallet)</b>	40 Pcs.
<b>Box Length/Depth</b>	970 mm
<b>Box Width</b>	130 mm
<b>Box Height</b>	68 mm
<b>Cardboard Packaging (Recycling symbol "20" PAP) per Pcs.</b>	0.024 kg
<b>Total Tare Weight</b>	0.024 kg
<b>Gross Weight</b>	0.14 kg
<b>Cubic metre</b>	1.9E-05 M3
<b>GTIN-13 Number</b>	5705020535154
<b>GTIN-14 Number (Box quantity)</b>	15705020535151
<b>Customs Tariff Number</b>	72230091

## Compliance & Standard Details

<b>Complies with (EC) 1935/2004 on food contact materials<sup>1</sup></b>	Yes
---	-----

## Item Number: 53515

Complies with EU Regulation 2023/2006/EC of Good Manufacturing Practice	Yes
Complies with FDA Regulation CFR 21 <sup>1</sup>	Yes
Complies with UK 2019 No. 704 on food contact materials	Yes
Complies with REACH Regulation (EC) No. 1907/2006	Yes
Complies with California Proposition 65	Yes
Complies with Halal and Kosher	Yes
PFAS intentionally added	No

## Technical Data

Product Diameter	5 mm
------------------	------

## Usage Limits

Recommended sterilisation temperature (Autoclave)	121 °C
Max. cleaning temperature (Dishwasher)	93 °C
Max usage temperature (food contact)	100 °C
Max usage temperature (non food contact)	100 °C
Min. usage temperature <sup>3</sup>	-20 °C
Max. drying temperature	120 °C
Min. pH-value in usage concentration	2 pH
Max. pH-value in Usage Concentration	10.5 pH

New equipment should be cleaned, disinfected, sterilised and any labels removed, as appropriate to its intended use, e.g. high risk vs. low risk food production areas, general hospital areas vs. intensive care units, before use.